



**Tolerances**

Shaft dia: f7 (< 55 mm id.)  
 h8 (> 55 mm id.)  
 Housing: H7

**Material: Triple-layer bushing**

Copper plated steel-layer (anti-corrosive)  
 Sintered, multiporous bronzelayer  
 Acetal plastic layer (with grease pockets)

Chamfer: Inner and outer ends

This document and its contents are the exclusive property of Lagermetall AB, and may not be copied, reproduced, transmitted or communicated to a third party, or used for any purpose without written permission.

|                        |                                                 |                            |                                                    |                                            |                                  |
|------------------------|-------------------------------------------------|----------------------------|----------------------------------------------------|--------------------------------------------|----------------------------------|
|                        | <br>IRONCAD 2D drawing<br>3D model is available | General Tolerances acc to: | File Name:<br><b>440-POM-LMB.icd</b>               | Template Created Date:<br>2016-08-16 12:59 |                                  |
|                        |                                                 | ISO 2768-mK                | Drawn by: <b>UP</b>                                | Weight g: <b>2118.97</b>                   | Material:<br><b>Triple-layer</b> |
| <br>www.lagermetall.se |                                                 |                            | Wrapped triple-layer bearing<br>with acetalplastic |                                            | Sheet No: <b>1 ( 1 ) ...</b>     |
|                        |                                                 |                            |                                                    |                                            | Rev.                             |