



**Tolerances**

Shaft dia: e7 / f7

Housing: H7

Extra hard, up to 150 HB

Material: Cu Sn8

Cu - 91,3%

Sn - 8,5%

P - 0,2%

Chamfer: Inner and outer ends

This document and its contents are the exclusive property of Lagermetall AB, and may not be copied, reproduced, transmitted or communicated to a third party, or used for any purpose without written permission.

|  |   |  |  |                                   |                                    |   |
|--|---|--|--|-----------------------------------|------------------------------------|---|
| <p><b>A4</b><br/>ISO E</p>                       | <p>IRONCAD 2D drawing<br/>3D model is available</p> | <p>General<br/>Tolerances acc to:<br/><b>ISO 2768-mK</b></p> | <p>File Name:<br/><b>490-AB090.icd</b></p> |                                   |                                    | <p>Template Created Date:<br/><b>2016-08-16 12:49</b></p> |
|  |   |  | <p>Drawn by:<br/><b>UP</b></p>             | <p>Weight g:<br/><b>63.67</b></p> | <p>Material:<br/><b>Cu Sn8</b></p> | <p>Drawing Created Date:<br/><b>2016-09-24</b></p>        |
| <p><b>LAGERMETALL</b><br/>www.lagermetall.se</p> |   |  | <p>Wrapped bushing<br/>Type AB090</p>      |                                   |                                    | <p>Sheet No: <b>1 ( 1 ) ...</b></p>                       |
|  |   |  |  |                                   |                                    | <p>Doc. No:<br/><b>490-AB090-3435</b></p>                 |