



**Tolerances**

Shaft dia: f7 (< 55 mm id.)  
 h8 (> 55 mm id.)  
 Housing: H7

**Material: Triple-layer bushing**

Tinplated steel-layer (anti-corrosive)  
 Sintered, multiporous bronzelayer  
 PTFE sliding surface (selflubricating)

Chamfer: Inner and outer ends

This document and its contents are the exclusive property of Lagermetall AB, and may not be copied, reproduced, transmitted or communicated to a third party, or used for any purpose without written permission.

|                            |   |   |                                      |                            |                                    |  |
|----------------------------|---|---|--------------------------------------|----------------------------|------------------------------------|--|
| <p><b>A4</b><br/>ISO E</p> | <p>IRONCAD 2D drawing<br/>3D model is available</p> | <p>General Tolerances acc to:<br/>ISO 2768-mK</p> | <p>File Name:<br/>400-BM-LMB.icd</p> |                            |                                    | <p>Template Created Date:<br/>2016-08-16 12:46</p> |
|                            |   |   | <p>Drawn by:<br/>UP</p>              | <p>Weight g:<br/>40.12</p> | <p>Material:<br/>Triple-layers</p> | <p>Drawing Created Date:<br/>2016-09-19</p>        |
| <p>www.lagermetall.se</p>  |   |   | <p>Wrapped bushing BM-LMB</p>        |                            |                                    | <p>Sheet No:<br/>1 ( 1 ) ...</p>                   |
|                            |   |   |                                      |                            |                                    | <p>Rev.<br/>...</p>                                |