



Tolerances

Shaft dia: f7 (< 55 mm id.)

h8 (> 55 mm id.)

Housing: H7

Material: Triple-layer bushing

Tinplated steel-layer (anti-corrosive)

Sintered, multiporous bronzelayer

PTFE sliding surface (selflubricating)

Chamfer: Inner and outer ends

This document and its contents are the exclusive property of Lagermetall AB, and may not be copied, reproduced, transmitted or communicated to a third party, or used for any purpose without written permission.

| | | | | | | |
|-------------------------------|---|--|--|---------------------------|------------------------------------|--|
| <p>A4</p> <p>ISO E</p> | <p>IRONCAD 2D drawing 3D model is available</p> | <p>General Tolerances acc to:</p> <p>ISO 2768-mK</p> | <p>File Name: 410-BM-F-LMB.icd</p> | | | <p>Template Created Date: 2016-08-16 12:46</p> |
| | | | <p>Drawn by: UP</p> | <p>Weight g: 4.30</p> | <p>Material: Triple-layers</p> | <p>Drawing Created Date: 2016-09-19</p> |
| <p>www.lagermetall.se</p> | | | <p>Wrapped bushing flange BM-LMB</p> | | | <p>Sheet No: 1 (1) ...</p> |
| | | | | | | <p>Rev. ...</p> |