



Tolerances

Shaft dia: f7 (< 55 mm id.)

h8 (> 55 mm id.)

Housing: H7

Material: Triple-layer bushing

Copper plated steel-layer (anti-corrosive)

Sintered, multiporous bronzelayer

Acetal plastic layer (with grease pockets)

Chamfer: Inner and outer ends

This document and its contents are the exclusive property of Lagermetall AB, and may not be copied, reproduced, transmitted or communicated to a third party, or used for any purpose without written permission.

<p>A4</p> <p>ISO E</p>	<p>IRONCAD 2D drawing 3D model is available</p>	<p>General Tolerances acc to:</p> <p>ISO 2768-mK</p>	<p>File Name:</p> <p>440-POM-LMB.icd</p>	<p>Template Created Date:</p> <p>2016-08-16 12:59</p>	
		<p>Drawn by:</p> <p>UP</p>	<p>Weight g:</p> <p>3.36</p>	<p>Material:</p> <p>Triple-layer</p>	<p>Drawing Created Date:</p> <p>2016-09-21</p>
<p>www.lagermetall.se</p>			<p>Wrapped triple-layer bearing with acetalplastic</p>		<p>Sheet No:</p> <p>1 (1) ...</p>
					<p>Doc. No:</p> <p>440-POM1412LMB</p>